



DuraSpec 125 Plus

Siding Insulation



DuraSpec



DuraSpec 125 Plus Siding Insulation is a closed cell EPS that meets or exceeds ASTM C578. With high retained R-value, this product provides great compressive strength (PSI), increase thermal efficiency and reduces energy costs.

DuraSpec Expanded Polystyrene (EPS) Siding Insulation is compatible with all types of siding - wood, aluminum, steel, fiber cement and vinyl.

- ***Retains R-value***
- ***Low water absorption***
- ***Cost effective***
- ***Easy to handle, install and cut***
- ***Environmentally friendly containing no CFCs or HCFCs***
- ***Various densities for job specifications***

DuraSpec 125 Plus EPS Properties

Thickness	R-Value @ 40° F	R-Value @ 75° F	PSI CR @ 10%
3"	12.75	11.76	13.0
2"	8.50	7.84	13.0
1.5"	6.38	5.88	13.0
1"	4.25	3.92	13.0
.75"	3.19	2.94	13.0
.5"	2.13	1.96	13.0

Availability

4' x 4', 4' x 8' and 4' x 16'
custom sizes available

Plymouth Foam
1800 Sunset Dr.
Plymouth, WI 53073

920-889-0021
800-669-1176

Contact

John Calkins 920-889-0021 jcedisonassc@yahoo.com

This brochure is printed by JC Edison & Associates for promotional use only.

*Check Plymouth Foam's website for additional information.