



# DuraSpec 150 HD

## Siding Insulation



DuraSpec



DuraSpec 150 HD Siding Insulation is a closed cell EPS that meets or exceeds ASTM C578. With high retained R-value, this product provides great compressive strength (PSI), increase thermal efficiency and reduces energy costs.

DuraSpec Expanded Polystyrene (EPS) Siding Insulation is compatible with all types of siding - wood, aluminum, steel, fiber cement and vinyl.

- ***Retains R-value***
- ***Low water absorption***
- ***Cost effective***
- ***Easy to handle, install and cut***
- ***Environmentally friendly containing no CFCs or HCFCs***
- ***Various densities for job specifications***

### DuraSpec 150 HD EPS Properties

Thickness	R-Value @ 40° F	R-Value @ 75° F	PSI CR @ 10%
3"	13.65	12.51	15.0
2"	9.19	8.34	15.0
1.5"	6.83	6.26	15.0
1"	4.55	4.17	15.0
.75"	3.41	3.13	15.0
.5"	2.28	2.09	15.0

### Availability

4' x 4', 4' x 8' and 4' x 16'  
custom sizes available

Plymouth Foam  
1800 Sunset Dr.  
Plymouth, WI 53073

920-889-0021  
800-669-1176

### Contact

John Calkins 920-889-0021 [jcedisonassc@yahoo.com](mailto:jcedisonassc@yahoo.com)