



Gold-Guard ^{HD} Siding Insulation



Gold-Guard HD is siding insulation board is a 2 sided, high barrier facer that offers rigidity and strength. This closed cell EPS board is ideal in re-cover applications or new construction. It is well-suited for all types of siding. Gold-Guard is a resilient product that holds its R-value and is resistant to bacteria, fungus, rot, mold and mildew.

Gold-Guard offers a stable R-value, dimensional stability, excellent water resistance and compressive strength properties. Facers can be clear or reflective.

- *Great for retro-fit applications*
- *No off-gassing*
- *1/2" - 4" thickness (4'x8')*
- *Light-weight, high strength*
- *Compatible with all siding types*
- *9.52 R-Value (2" - type II @ 25°F)*



Gold-Guard HD EPS Properties

Thickness	R-Value @ 40° F	R-Value @ 75° F	PSI CR @ 10%
3"	13.65	12.51	15.0
2"	9.19	8.34	15.0
1.5"	6.83	6.26	15.0
1"	4.55	4.17	15.0
.75"	3.41	3.13	15.0
.5"	2.28	2.09	15.0

Availability

4' x 8'

Contact

John Calkins 920-889-0021 jcedisonassc@yahoo.com

This brochure is printed by JC Edison & Associates for promotional use only.
Check Plymouth Foam's website for additional information.

Plymouth Foam
1800 Sunset Dr.
Plymouth, WI 53073
920-889-0021
800-669-1176