



Gold-Guard Neopor Siding Insulation



Plymouth Foam
1800 Sunset Dr.
Plymouth, WI 53073
920-889-0021
800-669-1176

Gold-Guard Neopor is siding insulation board is a 2 sided, high barrier facer that offers rigidity and strength. This closed cell Neopor EPS board is ideal in re-cover applications or new construction. It is well-suited for all types of siding. Gold-Guard is a resilient product that holds its R-value and is resistant to bacteria, fungus, rot, mold and mildew.

Gold-Guard offers a stable R-value, dimensional stability, water resistance and compressive strength. It is available clear or reflective.

- **Great for retro-fit applications**
- **No off-gassing**
- **1/2" - 4" thickness (4'x8')**
- **Light-weight, high strength**
- **Compatible with all siding types**



Tough

Gold-Guard Neopor EPS Properties

Thickness	R-Value @ 23° F	R-Value @ 75° F	PSI CR @ 10%
3"	15.03	13.44	13.0
2"	10.02	8.96	13.0
1.5"	7.52	6.72	13.0
1"	5.01	4.48	13.0
.75"	3.78	3.36	13.0
.5"	2.51	2.24	13.0

Availability

4' x 8'

Contact

John Calkins 920-889-0021 jcedisonassc@yahoo.com

This brochure is printed by JC Edison & Associates for promotional use only.
Check Plymouth Foam's website for additional information.